## LIFTING TECHNOLOGY PIT JACK

**MPJ 16.5/750 1S HM** VP 454275





#### MPJ 16.5/750 1S HM

VP 454275

The pit jack, which is mounted in a suspended position, lifts up to 16,5 t. The overhead rail pit jack, with deep-drawn chassis and long 750 mm stroke, is suitable for work with or without axle crossbeams and support systems. The manual hydraulic drive can be expanded with a pneumatic speed control function for fast piston rod movement. For lifting under load, an air motor can be additionally installed. For optimal pit adaptation, the chassis is adjustable by 140 mm.

#### PRODUCT DETAILS/ACCESSORIES

1-stage telescopic, rail-guided, suspended

#### Description:

Manual pit jack

with hand pump for load lifting

Specifically for wheel and brake works and dismantling smaller assemblies in conjunction with axle lifting beams and support systems for trucks and buses with 16.5 t load capacity

#### Control:

- Precision, user-friendly hand pump for fast stroke and lift
- Delicate and precision lowering of the pit jack with tried & tested system with integrated dead man's control

#### Design:

- For precise movement, the pit jack is rail-guided at the top edge of the pit
- Guarantees easy movement of the pit jack since all rollers are fitted with needle bearings crossways and lengthways

- Long total stroke of 750 mm to reach high-up units
- The pit jack is fitted with a downward deep-drawn P carriage for integrating an axle lifting beam at any height
- Alternatively, a straight S carriage can be used too
- Variable modular carriage system for various pit widths (700 -1200 mm) in conjunction with different roller versions and clearance degrees for adapting to work pit circumstances
- Corrosion-resistant piston rods thanks to self-lubrication
- High-quality powder-coating protects against corrosive liquids and elevates quality look and feel on a lasting basis

#### Scope of delivery:

- · Pit jack with hand pump
- · Deep-drawn P carriage and rollers for rails
- Standard support lugs 120 x 120 mm
- Operating instructions
- · EC conformity certificate
- · Colour: Jack base frame RAL 7040
  - Attachments and carriage RAL 7016

#### **TECHNICAL DATA**

Load capacity (CE)	16,500 kg
Stroke distance	750 mm
Lifting levels	1
Min. pick-up height from roller slide rail	- 69 mm
Pit jack depth for roller slide rail	1070 mm
Max. lifting height above roller slide rail	681 mm
Slide rail width inner dimensions	700 1200 mm
Carriage adjustable range	140 mm
Roller rest width	40 mm
Roller rest incline	8 % / 4.6°
Max. parallelism deviation slide rails	10 mm
Roller diameter (at the flange)	80 (95) mm
Support diameter inside/outside	45/70 mm

# LIFTING TECHNOLOGY PIT JACK

### **MPJ 16.5/750 1S HM** VP 454275



#### **TECHNICAL DATA**

Piston rod diameter	70 mm
Oil quantity/quality	9.51/ HLP-D 10
Drive	Manual hydraulic
Operating pressure	254 bar
Weight	239 kg

#### **ACCESSORIES**

ACCESSORIES - CARRIAGE		VZ 975569	
VZ 975923	S-carriage for suspended pit jacks up to 16.5 t	V7 07F 400	45 mm MODEL: PS-N
	-EXTRA CHARGE-	VZ 975409	Wooden Lifting Pad, 6 - 16 t Load Capacity, Prismatic Design, MODEL: HP 06-16
	Offset rollers for suspended pit jacks of up to 16.5 t -EXTRA CHARGE-	VZ 975287	Lifting Pad w. Rubber Surface, 11 t Load Capacity
VZ 975924	Cylindrical rollers for suspended pit jacks in pit profile rails	VZ 975289	MODEL: RPG 10 Plug-In Extender, L = 100 mm, MODEL: ZS 100/45
VZ 975562	Special rollers f. suspended and rail-quided pit	VZ 975290	Plug-In Extender, L = 150 mm, MODEL: ZS 150/45
VZ 37 000Z	jacks -EXTRA CHARGE-	VZ 975410	Plug-In Extender, L = 200 mm MODEL: ZS 200/45
ACCESSORIES - TRAVERSES, SUPPORT BRIDGES, SUPPORT SYST.		VZ 971221	Support Plate Extension 100 mm galvanized (2
VZ 975670	Self-locking axle lifting beam with 14.5 t support system MODEL: SAT 14.5-760	VZ 975330	pcs.) Diameter of supports 35 mm Support Tube L = 400 mm, Load Capacity: 20 t
VZ 975813	Self-locking axle lifting beam with 14.5 t support		(Pin Diam. 45 mm)
	system MODEL: SAT 14.5-820	VZ 975331	Support Tube L = 600 mm, Load Capacity: 20 t (Pin Diameter 45 mm)
VZ 975622	Self-locking axle lifting beam with 14.5 t support system MODEL: SAT 14.5-910 STOCK	VZ 975571	Support Tube L = 800 mm, Load Capacity: 15 t
VZ 975741	Self-locking axle lifting beam with 14.5 t support	VZ 975414	(Pin Diameter 45 mm) Spacer Block for Support Systems TAB (100 x
VZ 975743	system MODEL: SAT 14.5-910L SAT Rollers Retrofit Kit, Spring Mounted, with	VZ 370414	140 x 450 mm)
VZ 97 37 43	Plastic Rollers	VZ 975732	Gearbox Plate, Load Cpc. 1.0t Model: GP 1000
VZ 975814	SAT Wheel Deflector Plates (2 pcs)	VP 975915	Gearbox Mounting Tool with swivelling flat
VZ 975820	Spacer Block for Support Systems SAT (65 x 110	V7 07E016	supports MODEL: GMT 800
	x 320 mm)	VZ 975916 VZ 975917	Swivel supports for GMT 800 w. locking function Angle clamp supports for GMT 800 with rubber
VZ 975903	Axle lifting beam up to 15 t Adjustment range max. 1010 mm MODEL: AT 15		paď
VZ 975688	Axle Traverse Length Variation	VZ 975918	Semicircular flex supports for GMT 800 with rubber pads
VZ 975906	Axle traverse Long for busses, com. vehicles, 16.5t load cap. MODEL: AT 16.5 L1500	VZ 975611	Pit crossing continuously adjustable for pits w/o
VZ 975696	Axle Crossbar Load Capacity 3.5 t Model: ATV 3.5	VZ 07F610	wheel guides
VZ 975925	Support bridge for axle traverses up to 14.5 t load capac. MODEL: TAB 15	VZ 975612	Pit crossing continuously adjustable for pits with wheel guides
VZ 975326	Support Bridge AB w/o Centre Cut-Out up to 14,5	VZ 975613	Railings for pit crossing continously adjustable
	t Load Cpc. MODEL: AB 15	SUPPLEMENTARY CHARGES	
VZ 975686	Support System Version D/F	VT 998106	Transportkosten Grubenheber Abstützsystem,
VZ 975687	Support System Version E	VT 000100	Getriebeplatten
	ES - LOAD LIFTING PADS, LIFTING PADS, EXTENDERS,	VT 998108	Transportkosten Abstützsystem, Getriebeplatten
SUPPORT T		VIVI 996148 VV 997598	Montagekosten Grubenheber
VZ 975280	Narrow Lifting Pad, 20 t Load Capacity, galvanized, up to 100 mm (Pin Diameter 45 mm)		-EUROPE-
VZ 975285	Large Lifting Pad, galvanized, Load Capacity 20 t MODEL: GP 175/20	VV 997599	Packaging Suspended pit jack stackable -EUROPE/OVERSEAS-
VZ 975283	Large Lifting Pad, galvanized, Load Capacity 16.5 t MODEL: GP 220	VV 997601	Packaging Lifting beams, gearbox plates, stackable -EUROPE/OVERSEAS-