LIFTING TECHNOLOGY

MOBILE COLUMN LIFT

RGA UC VP 451179





RGA UC VP 451179

The mobile wheel engaging COLUMNLIFT RGA UC lifts up to 7.5 t per column and is equipped with an adjustable universal lifting carriage. Streamline column design offers a good overview when manoeuvring. The low-maintenance, electro-mechanical drive system ensures extremely smooth running while the excellent mechanical rigidity of the columns guarantees safety and the ability to function in any condition. A high-quality worm gear motor enables precision height positioning without overrun. Column communication is via wireless connection, the power supply via batteries.

PRODUCT DETAILS/ACCESSORIES

- Very smooth running due to electro-mechanical drive system
- High efficiency thanks to smooth-running, low-maintenance ball screw
- 5-year warrantee for entire spindle drive
- Excellent lifting column mechanical rigidity guarantees safety and function under any conditions
- Lifting columns can be moved conveniently and easily thanks to hydraulic dolly at each column
- Precision-height positioning without overrun thanks to highquality worm gear motor
- Lifting carriages with adjustable universal support
- Generous adjustment range, also suitable for large wheel diameters
- · Overhead drive unit creates even more space in the work area
- · Workshop-robust and splash-proof control unit
- · Wear-free and easy-to-use membrane keypad
- Flexible column positioning thanks to battery power supply (4 x 12 V), guaranteeing suitability across all vehicle categories
- User convenience with panel operator controls on each individual column

- High level of flexibility in use due to different operating modes
- Group and individual column operating modes enable quick and easy replacement of wheel and axle suspensions
- Microprocessor control and wireless monitoring of movement synchronisation and all safety functions
- Útmost safety thanks to mechanically independent locking device
- Simple emergency lowering for power failure included as standard
- · System can easily be expanded with up to eight columns
- Streamline COLUMNLIFT design aids manoeuvrability specifically in workstations with restricted space
- · High-quality powder coating:
 - Window Grey, RAL 7040 (Columns)
 - Anthracite, Grey RAL 7016 (Lifting carriages)

Scope of delivery:

- 4 individual mobile columns with battery power supply
- · 4 hydraulic dollies

TECHNICAL DATA

Load capacity CE per column	7500 kg
Drive power per column	1.5 kW
Weight per column	545 kg
Lifting distance	1750 mm
Raising/lowering time	113 s
Tyre diameter min max.	550 - 1500 mm
Fork length	380 mm
Voltage for charger	230 V
Lifting cycles partial load (3500 kg)	35
Lifting cycles full load	25
Protection rating	IP 54

LIFTING TECHNOLOGY MOBILE COLUMN



ACCESSORIES

LIFT

VZ 971585	Single Post RGA UC 7500 kg lifting capacity with hydr. dolly	VZ 971289	Support Plate APV II -Squarefo 6-07/12/20
VP 451180	Single Post RGA UC -SUBSEQUENT DELIVERY Lifting capacity 7500 kg	VZ 971290	Support Plate APVV II -Square Support Stand AB 6-07/12/20
VZ 971588	Flat support forks for forklift trucks 1 set (2 pcs)	VZ 971168	Screw Adjustment SP 75 for A
VZ 971286	Cable Remote Control KFB2 for Mobile Column		Support Stands
	Lift	VZ 971310	Crossbar for Support of Semi
VZ 971164	Support Stand AB 6-07, lifting capacity 7500 kg, adjustment range 470 - 795 mm (each)		Pin
		VZ 971546	Transverse Beam TR8 32 Loa
VZ 971165	Support Stand AB 6-12, lifting capacity 7500 kg, adjustment range 875 - 1395 mm, mobile	VZ 971347	Transverse Beam TR10-32 Lo
		SUPPLEMENTARY CHARGES	
VZ 971166	Support Stand AB 6-20, lifting capacity 7500 kg,	VT 995698	Transportkosten 4 Einzelsäule
	adjustment range 1200-1965 mm, mobile	VT 995699	Transportkosten 6 Einzelsäule
VZ 971287	Support Plate APR II -Roundpluggable, for	VT 995703	Transportkosten 8 Einzelsäule
	Support Stand AB 6-07/12/20	VM 996077	Installation costs for mobile c
VZ 971288	Support Plate APRV II -Roundadjustable, for	VV 997560	Transport cradle for mobile co
	Support Stand AB 6-07/12/20	VV 997300	each containing 2 columns
			cacif containing 2 columns

VZ 971289	Support Plate APV II -Squarefor Support Stand AB 6-07/12/20			
VZ 971290	Support Plate APVV II -Squareadjustable, for Support Stand AB 6-07/12/20			
VZ 971168	Screw Adjustment SP 75 for AB 6-07/12/20 Support Stands			
VZ 971310	Crossbar for Support of SemiTrailers with 2 King Pin			
VZ 971546	Transverse Beam TR8 32 Load capacity 8t			
VZ 971347	Transverse Beam TR10-32 Load capacity 10t			
SUPPLEMENTARY CHARGES				
VT 995698	Transportkosten 4 Einzelsäulen inkl. Verpackung			
VT 995699	Transportkosten 6 Einzelsäulen inkl. Verpackung			
VT 995703	Transportkosten 8 Einzelsäulen inkl. Verpackung			
VM 996077	Installation costs for mobile column lifts			
VV 997560	Transport cradle for mobile columns (horizontal)			