## LIFTING TECHNOLOGY TWO POST LIFT

### **MA STAR 3.5 S STOCK** VP 251231





#### **MA STAR 3.5 S STOCK**

#### VP 251231

The 5-star lift MA STAR 3.5 A, which features stable torsion-resistant columns of rolled H-section steel, lifts cars and vans of up to 3.5 t. Symmetrical columns ensure that the lift width is kept to a minimum. The two post lift guarantees triple safety thanks to its spindle nut package, patented "giraffe" nut breakage detection and motor brake. The MA STAR also impresses with its straightforward plug and play commissioning as well as its intuitive, LED-based operation.

STOCK version - available ex stock.

#### PRODUCT DETAILS/ACCESSORIES

STOCK version - available ex stock

• RAL 7040 -

#### Description:

- · Load capacity 3500 kg
- · triple safety
- · Symmetrical columns for small overall width
- Symmetrical support arms
- Support arms swivelling 95°Variable installation width
- High-quality powder coating:
  - Window grey, RAL 7040 (columns)

Anthracite grey, RAL 7016 (lifting carriages, support arms)

#### Scope of delivery:

- 2 symmetrical columns with operating unit
- 4 symmetrical support arms (4 double telescopic)
- · Support disc plug-in system
- Cable bridge
- Spindle oil (0.5 l)
- · Operating instructions
- CE Declaration of Conformity
- Transport packaging

#### TECHNICAL DATA

Load capacity CE	3500 kg
Max. lifting height	1995 mm
Lifting / lowering time (load-dependent)	approx. 40/40 s
Bottom clearance of the support arms	100 mm
Adjustment range, support disc	80 - 110 mm
Extension range, support arms	630 - 1240 mm
Overall width*	3557 mm
Outside base plates*	3307 mm
Outside columns*	3097 mm
Inside columns*	2700 mm
Drive-through width	2200 - 2400 mm
Column height	2943 mm
Max. overall height (with cable bridge)	4499 mm
Drive power	2 × 3.0 kW
Power supply	3/N/PE 400 V 50 Hz
Fuse	C16 A
Weight	640 kg

# LIFTING TECHNOLOGY TWO POST LIFT

## **MA STAR 3.5 S STOCK** VP 251231



#### TECHNICAL DATA

Packaging dimensions (L x W x H)

2900 x 1100 x 710 mm

Required concrete quality C 20/25

Required thickness of concrete slab w/o screed min.

180 mm

#### **ACCESSORIES**

ACCESSORI	ES COLUMNS	VZ 975050	Non-skid device for vehicles with longitudinal	
VZ 990488	Power Set mounted to Operating Column		frame up to 100 mm width (2 pcs)	
VZ 990500	Power Set mounted to Operating Column	VZ 971649	Strap attachment on support arm thread for tilt protection	
VZ 971590	Additional Operating Panel at Opposite Column MA STAR 3.5 incl. emergency-stop button	VZ 971227	Special Prism Support for MB G-Class w/o Tread Plate Plug-In System - (4 pcs.)	
VZ 990489	Power Set mounted to Opposite Column	VZ 971520	Special Prism Support for MB G-Class with Tread	
VZ 990501	Power Set mounted to Opposite Column	VZ 971320	Plate Plug-In System - (4 pcs.)	
VZ 990504	Power Set mounted to Operating Column	VZ 971539	Storage Tray MAHA stainless steel, magnetic for	
VZ 990505	CE Stop beeper volume adjustable -EXTRA CHARGE-		small parts, (2 pcs)	
VZ 990503	Socket combination Energy box	ACCESSORI	ACCESSORIES SAFETY SYSTEMS	
VZ 971591	Holder for Pneumatic Air Wrench and 6 Sockets	VZ 971104	Light Barrier Safety Device to avoid Contact with Ceiling	
VZ 971592	Document Holder, suitable for column/wall mounting (1 pcs.)		FURTHER ACCESSORIES	
VZ 971593	Holding Device for 2 Support Plate Extensions,	VZ 971601	Drilling template for MA STAR 3.5 S	
	can be mounted to Lift (1 pcs.)	VZ 971606	Set-up device for MA STAR 3.5 A/S	
VZ 971224	Holding Device for 2 Support Plate Extensions,	VZ 971603	Add. Ground Plates (2 pcs) for	
	can be mounted to Wall (2 pcs.)	VZ 971605	CEE coupler 16A for on-site connection	
VZ 990493	LED light (1 pce) pluggable	VZ 990490	Socket for inground wiring	
VZ 971607	Door stop (2 pcs) on lifting carriage for vehicles with low doors	SUPPLEMEN	SUPPLEMENTARY CHARGES	
VZ 971615	Perforated plate modules in in L-shape for	VT 998047	Transport Zweisäulen-Hebebühne MAHA direkt	
VZ 37 1010	Hoffmann GARANT Easyfix	VT 998048	durch Werksverkehr bis 3500 kg Tragl. (1-4 Stück) Transport Zweisäulen-Hebebühne MAHA direkt	
ACCESSORI	ES SUPPORT ARMS	V1 990040	durch Werksverkehr bis 3500 kg Tragl. (4-9 Stück)	
VZ 971346	Special Support (4 pcs) for AUDI TT/TTS/TT RS, suitable f. Lifting Points of Vehicle Jack	VT 998049	Transport Zweisäulen-Hebebühne MAHA direkt durch Werksverkehr bis 3500 kg Tragl. (ab 10 St.)	
VZ 971247	Support Plates for VOLVO external diameter 100 mm plug-in system- (4 pcs.)	VM 995024	Installation costs Two-post lift, electromechanical load capacity 3500 kg	
VZ 971220	Support Plate Extension 50 mm, galvanized, (2	VM 996232	Montagekosten Energieset	
	pcs.) Diameter of supports 35 mm	VM 996233	Montagekosten zusätzliche Bedieneinheit an	
VZ 971221	Support Plate Extension 100 mm galvanized (2		Gegensäule	
	pcs.) Diameter of supports 35 mm	VM 996072	Install. Charges f. Ceiling Light Barrier -T&M Basis	
VZ 971222	Support Plate Extension 150 mm galvanized (2 pcs.) Diameter of supports 35 mm	VM 999080	Install. material Injection system for MA STAR 3.5 S MA STAR 5.5	
VZ 971223	Support Plate Extension 200 mm galvanized (2 pcs.) Diameter of supports 35 mm	VM 999054	Install. material Injection system for MA STAR 3.5 A/S	
		VM 999081	Injection mortar Cartridge 500 ml (1 pce)	